



Horses

Clean paddocks for healthy horses. With the Trilo vacuum sweepers you can clean up your paddocks fast. With the wandering hose you you can collect the droppings in the paddocks and stables. With the cut and collect system you can cut the grass and collect the droppings in one pass efficiently, so fresh grass growth is encouraged. The Trilo vacuum sweepers range from 2 cubic metres up to 20 cubic metres in hopper capacity and up to a working width of 6.5

metres. With the Trilo vacuum sweepers you can collect the horse droppings, grass-clippings and cut and collect. With various working widths and capacities, we can offer you the machine that fits best for you.

HIGH CAPACITY FAN

The heart of the Trilo vacuum units is the high capacity fan, giving it a high work rate, enabling you to collect



SG 300 collecting droppings



Suction hose



SU 40K cleaning stables



SU 40K



SG 1165



large amounts of droppings and clippings. The re-enforced, balanced fan wheel and the double walled casing, provide a wear resistant, reliable and above all, safe source of suction power. The impeller casing has an inspection trap in the lower part.

HIGH LOADING CAPACITY

Because of the powerful air flow the complete loading space can be filled tightly during operation. So large

amounts of material can be compacted in its hopper. By tipping cuttings away, or by the moving floor, neatly unloads with a simple flick of a lever. This way an area the size of a polo field or racecourse can be taken care of quickly and adequately.

The optional double-walled top cover, exhausts the air-flow downwards at the rear of the machine. At the same time the air is filtered by a coarse filter net.



SG400



Twisted Flail



Brush



SG 670 cleaning stables

SU 40 K

Fan:	Trilo Ø400 mm
Powered:	Honda GXV-340 8kW-11hp
Loading capacity:	2 m ³
Overall length:	3.65 m
Overall width:	1.26 m
Overall height:	1.74 m
Suction hose:	Ø 200mm x 3.5 m
Weight:	kg
Tires:	23 x 10.5
Hydraulics:	180 bar (optional electric)
Unloading:	Tipper

SG 300

Fan:	Trilo Ø700 mm
Transmission:	PTO @ 540 rpm
Horse power req:	21kW – 28 hp
Loading capacity:	3 m ³
Overall length:	3.90 m
Overall width:	1.70 m
Overall height:	1.74 m
Working width:	1.50m
Weight:	1.200 kg
Tires:	26.5X14.00-12
Hydraulics:	180 bar-40 Ltr
Unloading:	High tipper (1.6 m)

SG 400

Fan:	Trilo Ø850 mm
Transmission:	PTO @ 540 rpm
Horse power req:	31kW – 45 hp
Loading capacity:	4 m ³
Overall length:	4.50 m
Overall width:	1.90 m
Overall height:	2.05 m
Working width:	1.70 m
Weight:	1.300 kg
Tires:	19 x 17 10 Ply
Hydraulics:	180 bar-40 Ltr
Unloading:	High tipper (2 m)

SG 670

Fan:	Trilo Ø850 mm
Transmission:	PTO @ 540 rpm
Horse power req:	31kW – 45 hp
Loading capacity:	7 m ³
Overall length:	4.90 m
Overall width:	2.70 m
Overall height:	2.45 m
Suctionhood:	2.50 m
Weight:	1.280 kg
Tires:	19 x 17 10 Ply
Hydraulics:	180 bar-40 Ltr
Unloading:	conveyor floor

SG 1165

Fan:	Trilo Ø960 mm
Transmission:	PTO @ 540 rpm
Horse power req:	60kW – 82 hp
Loading capacity:	11 m ³
Overall length:	6.30 m
Overall width:	2.50 m
Overall height:	2.45 m
Working width:	6.50 m
Weight:	2.400 kg
Tires:	19 x 17 10 Ply(pending)
Hydraulics:	180 bar-40 Ltr
Unloading:	Tipper

Vanmac

Astronaut 40
 3824 MJ Amersfoort
 Tel.: +31 – 33 456 45 50
 Fax: +31 – 33 456 44 33
 E-mail: sales@trilo.com
 Internet: www.trilo.com